

# Commercial

# SlideSmart™ CNX



Slide Gate Operator

## Capability meets simplicity

Connected gate operator with advanced features of Smart DC, BlueBUS and OXI technology creating a best in class slide gate operator



Move up to 1,500 lb/ 50 ft gate



Intelligent charging system, monitors battery condition to maximize battery life



Super quiet, super reliable direct drive gear train



Easy system troubleshooting with onboard event log



Keep your gate moving after power loss: up to 4,000 ft/standard batteries and 18,000 ft extended batteries



Independent, field-adjustable open and close speeds



Field programmable to specific site requirements



Locking, tight fitting covers seal out rain and deters rodents and small pests



Real time system security alerts with integrated HyNet™ Gateway



5 year warranty  
7 year single-family




BlueBUS  
Photo Eye\*  
+ ASO Edge

Hardware included  
\*Through Beam



S.T.A.R.T. CNX™ installer smartphone app for full control from your phone

- Bluetooth connection to smartphones
- Intuitive to use
- Full control of operator settings



**MADE  
★ IN THE ★  
USA**  
WITH GLOBAL MATERIALS  
DESIGNED IN KENT, WA

# Residential and Commercial



Slide Gate Operator

## SlideSmart™ CNX Model, AC or Solar

Standard	SlideSmart CNX 15
Solar	Solar ready for 12 - 36V
Gate Weight Max.	1,500 lb (680 kg)
Gate Length Max.	50 ft (15 m)
Pull Force*	300 lb
Rate of Travel	0.75, 1 or 1.25 ft/s (23, 30 or 38 cm/s)** Open/Close speed set independently
Duty Cycle	Continuous
Horsepower	Equivalent to 1/2 hp
Drive	Electromechanical - 24V Brushless DC motor with direct drive power train
UPS Battery Backup Cycles***	Field configurable to fail open or secure when batteries deplete. Standard battery backup gate travel: Two 8Ah batteries. Up to 4,000 ft (1,219 m) after AC power loss. Extended battery backup gate travel: Two 35Ah batteries. Up to 18,000 ft (5,486 m) after AC power loss.
Temperature Rating	-13° to 158°F (-25° to 70°C)
Operating Voltage	24VDC
Input Voltage	Switch select 115V or 208-230V, 60/50 Hz; Solar input 12 or 24V solar panels
Accessory Power	24VDC at each input & SS relay (1A accumulative)
Communication	BlueBUS, USB, Ethernet, T4, RS-485, Bluetooth
User Controls	SmartCNX Controller with 70+ configurable settings. 32 character OLED display and 7 tactile buttons, or Bluetooth smartphone interface, for programming.
Relays	3 configurable user relays: Two - 30VDC, 3A solid state. One 250VAC, 10A electromechanical; Optional SmartCNX I/O Expansion module with 8 additional inputs supporting 10k, 0-5V (analog), and dry contact inputs
Finish	Zinc rich primer with black powder coated chassis. High impact copolymer cover.
ETL Listed (UL 325)	Usage Class I, II, III, IV**
Warranty	5 year (7 year single-family residential)

\* Nice HySecurity manufacturers only reliable and powerful gate operators and provides an extra margin of power to be certain the gate works in adverse conditions. Some manufactures overstate the length and weight capacity of their operators, but Nice HySecurity rates conservatively. Note that our pull force ratings are substantial and that extra margin of power is part of the HySecurity reputation for reliability.

\*\* Speed setting cannot be configured to exceed 1 ft/s for Class I and II usage.

\*\*\*The actual number of gate cycles available from battery depends upon gate resistance to travel, cycle length, battery size, state of charge and health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

To enable fully automatic operation, all SLIDE gate operators require a minimum of TWO monitored external entrapment protection sensors (one for each direction) to protect entrapment zones in both the open and close direction of travel.

### Optional Accessories



Battery Backup Kit - 35Ah



Hy5B™ 2.0 Vehicle Detector



Photo Eye Kits



Radio Receivers & Transmitters



ASO Edge Sensors

SlideSmart CNX and SwingSmart CNX require professional installation



D0941 111919