

Commercial











# SwingSmart™ CNX



Swing Gate Operator

## Capability meets simplicity

Connected gate operator with advanced features of Smart DC, BlueBUS and OXI technology creating a best in class swing gate operator

	Move up to 1,300 lb gate leaf		Patented Taper Clamp provides adjustable protection from high winds and gate strikes
	Universal Arm design has cast steel elbow housing and oval telescoping arms for safety and easy installation		Intelligent charging system, monitors battery condition to maximize battery life
	Keep your gate moving after power loss: 300 cycles/standard batteries and 1,200 cycles extended batteries		Easy system troubleshooting with onboard event log
	Field programmable to specific site requirements		Independent, field-adjustable open and close speeds
	Real time system security alerts with optional HyNet™ Gateway		5 year warranty 7 year single-family



**BlueBUS Photo Eye\***  
\*Through Beam Hardware included




Residential



Taper clamp

S.T.A.R.T. CNX™ installer smartphone app for full control from your phone

- Bluetooth connection to smartphones
- Intuitive to use
- Full control of operator settings



**MADE IN THE USA**  
WITH GLOBAL MATERIALS  
DESIGNED IN KENT, WA

# Residential and Commercial



Swing Gate Operator

## SwingSmart™ CNX Model, AC or Solar

Standard	<b>SwingSmart CNX 20</b>
Solar	Solar ready for 12 - 36V
Gate Specs	1,300 lb (590 kg) for 12 ft (4 m) leaf, 800 lb (363 kg) for a 16 ft (5 m) leaf, 600 lb (272 kg) for a 20 ft (6 m) leaf
Open/Close Time	Open/Close time set independently. Adjustable 10 to 15 seconds.
Duty Cycle	Continuous
Drive	Electromechanical - 24V Brushless DC motor with direct drive power train
Horsepower	Equivalent to 1/2 hp
UPS Battery Backup Cycles*	Field configurable to fail open or secure when batteries deplete. Standard battery backup gate cycles: Two 12V 8Ah batteries. Up to 300 cycles after AC power loss. Extended battery backup gate cycles: Two 12V 35Ah batteries. Up to 1,000 cycles after AC power loss.
Temperature Rating	-13° to 158° F (-25° to 70° C)
Operating Voltage	24VDC
Input Voltage	Switch select 115V or 208-230V, 60/50 Hz; Solar input 12 or 24V solar panels
Accessory Power	24VDC at each input & SS relay (1A accumulative)
Communication	BlueBUS, USB, Ethernet, T4, RS-485, Bluetooth
User Controls	SmartCNX Controller with 70+ configurable settings. 32 character OLED display and 7 tactile buttons or Bluetooth smartphone interface, for programming.
Relays	3 configurable user relays: Two - 30VDC, 3A solid state. One 250VAC, 10A electromechanical; Optional SmartCNX I/O Expansion module with 8 additional inputs supporting 10k, 0-5V (analog), and dry contact inputs
Finish	Zinc rich primer with black powder coated chassis. High impact copolymer cover.
ETL Listed (UL 325)	Usage Class I, II, III, IV
Warranty	5 year (7 year single-family residential)

\* The actual number of gate cycles available from battery depends upon gate resistance to travel, cycle length, battery size, state of charge and health, ambient temperature, accessory power draw and frequency of gate cycles during power outage.

To enable fully automatic operation, all SWING gate operators require a minimum of ONE monitored external entrapment protection sensor to protect entrapment zones in either the open or close direction of travel. However, an additional monitored sensor is required if there is a risk of entrapment in both directions of gate travel.

### Optional Accessories - See website for complete list



Battery Backup Kit - 35Ah



Photo Eye Kits



Radio Receivers & Transmitters



Hy5B™ 2.0 Vehicle Detector



ASO Edge Sensors

SlideSmart CNX and SwingSmart CNX require professional installation

