

Features:



Choice:

Architects and designers have options, including a variety of finishes, lighting designs, and foundations.



Clearance:

Shallow mount bollards when working around buried utilities, deep mount bollards for the smallest footprint.



Freedom:

Removable bollards allow occasional vehicle traffic without sacrificing security.



Security:

Fixed bollards protect buildings and equipment while adding to the overall aesthetic of the facility.



Made in USA:

Designed, tested and built within USA from globally sourced materials.



Bollards M30/M50

Fixed perimeter security with pedestrian access




Technical Specifications

| Model | Bollard M30D-F | Bollard M30D-R | Bollard M30S-F | Bollard M30S-R | Bollard M30S-L | Bollard M50D-F | Bollard M50D-R | Bollard M50S-F | Bollard M50S-R | Bollard M50S-L |
|-----------------|--|-------------------|-------------------|-------------------|----------------|-------------------|-------------------|-------------------|-------------------|---------------------------|
| Crash Certified | Engineered* | | | M30 P2 | Engineered* | M50 P1 | | M50 P2 | Engineered* | |
| Finish | Bollard: Hot dip galvanized, Zinc Rich Primer or Powder coat | | | | | | | | | |
| Lighted | Unl | | | ghted | Lighted | | ted | d Light | | |
| Above Grade | 36 inch | | | | 45-5/8 inch | 39 inch | | 36 inch | | 45-5/8 inch (FLAT CAP) |
| Foundation | 36 inch 12 | | | | | 44 inch | | 12 inch | | |
| Warranty | 1 year | | | | | | | | | |

^{*} Engineered - No crash testing performed; speed rating assigned per technical specifications; penetration rating undetermined

Bollard cap choices:



Lighted bollard choices:



Options

Finish options

Hot dip galvanized Powder coat Zinc rich primer

Light options

Glass refractor globe (dome cap) Stacked louver globe (flat cap) Cool colored LED (5000K) Warm colored LED (3000K)

Stainless steel cover options

304 or 316 stainless Flat cap Surface mount Domed cap Knight cap

Lighted bollard cover options

304 or 316 stainless Flat cap Surface mount Domed cap Slotted light opening Clear or opal lens 360° light opening

